




Engineered  
in Italy

**NEW**  
5 BUSBAR

## FU 240 / 245 / 250 P

Polycrystalline Photovoltaic Module - 54 Cells



Note: dimensions in mm

### GENERAL FEATURES

- **15-year product warranty**
- **High-efficiency cells** decrease ohmic losses and increase the yield
- **Tempered 3.2 mm safety glass** for optimal mechanical stability and transparency
- **High temperature resistance** (tested at 105° C for 200 hours)
- For installations **up to an altitude of 7000 m**
- Maximum **resistance against hail** (83 km/h)
- Quality control with **electroluminescence (EL) tests** on each module

### CERTIFICATIONS

- > **IEC 61215:2016 - IEC 61730:2016 & Factory Inspection**
- > **Fire Resistance - Class 1**
- > **Salt Corrosion Resistance**  
IEC 61701
- > **Ammonia Corrosion**  
IEC 62716
- > **PID Test - Class A**  
Potential Induced Degradation
- > **Dust and Sand Resistance**  
IEC 60068-2-68

**NEW**

### GUARANTEES

#### Performance guarantee

Max power decrease **0.5%/year**

97% at the end of first year


**90% at the end of 20<sup>th</sup> year**

87% at the end of **25<sup>th</sup> year**

#### Product guarantee

**15 YEARS**

■ Market standard performances  
■ FuturaSun performances



**NEW**

**NEW**

## ELECTRICAL DATA

MODULE		FU 240 P	FU 245 P	FU 250 P
<i>Standard Test Conditions STC: 1000 W/sqm - AM 1.5 - 25 °C - tolerance: Pmax (±3%), Voc (±4%), Isc (±5%)</i>				
Module power (Pmax)	W	240	245	250
Open circuit voltage (Voc)	V	34.09	34.40	35.17
Short circuit current (Isc)	A	9.03	9.11	9.17
Maximum power voltage (Vmpp)	V	27.78	28.11	28.49
Maximum power current (Impp)	A	8.65	8.73	8.80
Module efficiency	%	16.3	16.6	16.9

<i>Nominal Module Operating Temperature NMOT: 800 W/mq - T=45 °C - AM 1.5</i>				
Module power (Pmax)	W	175.63	179.29	182.95
Open circuit voltage (Voc)	V	31.30	31.58	32.29
Short circuit current (Isc)	A	7.42	7.48	7.53
Maximum power voltage (Vmpp)	V	25.16	25.46	25.80
Maximum power current (Impp)	A	6.99	7.05	7.11

## TEMPERATURE RATINGS

Temperature coefficient Isc	%/°C	0.0474
Temperature coefficient Voc	%/°C	-0.285
Temperature coefficient Pmax	%/°C	-0.37
NMOT *	°C	45
Operating temperature	°C	from -40 to +85

\* Nominal Module Operating Temperature

## MECHANICAL SPECIFICATIONS

Dimensions	1490 x 990 x 35 mm
Weight	16.5 kg
Glass	Tempered, transparent, 3.2 mm
Cell encapsulation	EVA (Ethylene Vinyl Acetate)
Cells	54 polycrystalline cells 156.75x156.75 mm
Backsheet	Composite multilayer film
Frame	Anodized aluminium frame with mounting and drainage holes
Junction box	Certified according to IEC 62790, IP 68 approved
Cables	Solar cable, length 900 mm assembled with MC4-combinable plugs
Maximum reverse current (Ir)	20 A
Maximum system voltage	1000 V (1500 V on request)

Authorized Dealer



**FuturaSun srl**

Riva del Pasubio, 14 - 35013 Cittadella - Italy  
Tel + 39 049 5979802 Fax + 39 049 0963081  
[www.futurasun.com](http://www.futurasun.com) - [info@futurasun.it](mailto:info@futurasun.it)

2018\_54p\_240-250\_en\_v2