

Polycrystalline



POLY AI-BSF | TECHNOLOGY INSIDE

280 W 17.14 %

Maximum power

Maximum efficiency


KEY BENEFITS AND FEATURES



Power **280 Watt**



60 M2 **Polycrystalline** cells



Silver frame and white backsheet



Revamping series - Specifically designed for replacement of old photovoltaic modules



Module current approx. **9 Ampere** to fit with old 6 inch solar cells



1650 x 990 x 35 mm

Performance guarantee


- **25-years** performance warranty with max power decrease from 2nd year **0.5%/year**
- **97%** at the end of first year
- **90%** at the end of 20th year
- **87%** at the end of 25th year

Product guarantees

- **15-year** product warranty
- Third-party product **liability** insurance
- All FuturaSun's modules are designed and guaranteed by the **Italian** headquarters

Mechanical Specifications

Dimensions	1650 x 990 x 35 mm
Weight	17.7 kg
Glass	High transmission, Low iron, Tempered, ARC, Thickness 3.2 mm
Cells	60 polycrystalline cells 156.75 x 156.75 mm
Frame	Anodized aluminium frame with mounting and drainage holes
Junction boxes	Certified according to IEC 62790, IP 68 approved, 3 bypass diodes
Cables	Solar cable, length 900 mm or customized assembled with 4mm ² compatible connectors
Backsheet	Composite Multilayer film - white
Maximum reverse current (I _r)	20 A
Maximum system voltage	1000 V (1500 V on request)
Mechanical load (snow)	Design load: 3600 Pa, (5400 Pa including safety factor 1.5)
Mechanical load (wind)	Design load: 1600 Pa, (2400 Pa including safety factor 1.5)



Electrical data - STC*

FU 280 M

Sorting tolerance	W	0/+5
Module power (P _{max})	W	280
Open circuit voltage (V _{oc})	V	39.00
Short circuit current (I _{sc})	A	9.21
Maximum power voltage (V _{mpp})	V	31.80
Maximum power current (I _{mp})	A	8.85
Module efficiency	%	17.14

Electrical data - NOCT**

FU 280 M

Module power (P _{max})	W	205
Open circuit voltage (V _{oc})	V	35.81
Short circuit current (I _{sc})	A	7.57
Maximum power voltage (V _{mpp})	V	28.80
Maximum power current (I _{mp})	A	7.15

Temperature ratings

Temperature coefficient I _{sc}	%/°C	0.05
Temperature coefficient V _{oc}	%/°C	-0.27
Temperature coefficient P _{max}	%/°C	-0.35
NOCT**	°C	45
Operating temperature	°C	from -40 to +85

Certifications

Factory	ISO 9001 - 14001 - 45001
Product	IEC 61730, IEC EN 61215, Fire Class C, IEC EN 61701, IEC EN 62716, Class 1 UNI9177, INMETRO, HW3

Packaging

Quantity / Pallet	30 - 35 pcs
Container 40' HC	910 pcs / 28 pallets

The information included in this module datasheet is subject to change without notice and is provided for informational purposes only. No contractual rights are established or should be inferred because of user's reliance on the information contained in this module datasheet. Please refer to the appropriate module user guide and module product specification document for more detailed technical information regarding module performance, installation and use.

*Standard Test Conditions STC: 1000 W/m² - AM 1.5 - 25 °C - tolerance: P_{max} (±3%), V_{oc} (±4%), I_{sc} (±5%)
 **Nominal Operating Cell Temperature NOCT: 800 W/m² - T=45 °C - AM 1.5

EN_03